

# 1100 / F1100

## Rim Exit Devices



### RIM

- Applications

### Doors & Preparations

- For all types of single and double doors with/without a mullion. For mullions, see page 33.
- For new or retrofit installation into other manufacturers' devices.
- 1-3/4" to 2-1/4" thick, up to 4' wide opening; for thicker doors, consult factory.
- Furnished standard for 1-3/4" thick, 3' wide opening.
- For maximum door opening applications and listings for Fire Exit Devices, see page 45.



### Specifications

Certification/Compliance	<ul style="list-style-type: none"><li>• Panic devices UL/cUL listed for UL305 and ANSI/BHMA A156.3 Grade 1 Panic Hardware.</li><li>• UL/cUL Fire rated for 3-hour Fire Exit Hardware, conforms to UL10C and UBC7-2. Also complies with NFPA 80 Fire doors and windows.</li><li>• Exit devices, levers, trims and pulls comply with American Disability Act (ADA) and NFPA 101 life safety code.</li></ul>	
Center Case	<ul style="list-style-type: none"><li>• Universal center case, heavy wrought steel and sintered metal parts.</li><li>• Device functions are determined by adaptation with type of trim.</li></ul>	
Strikes	<b>Panic</b> P/N. 106 (roller type)	<b>Fire</b> P/N. 108 (roller type)
	See page 25.	
Dogging	<ul style="list-style-type: none"><li>• NOT available on Fire Exit Hardware.</li><li>• Dogging options available for LD, CD, ED (ELR). See page 32.</li><li>• Flat/Hex key dogging standard.</li></ul>	
Fasteners	<ul style="list-style-type: none"><li>• Machine screws and wood screws are furnished standard.</li></ul>	
Sex Bolts (SNB)	<ul style="list-style-type: none"><li>• Required when used with wood, composite or non-reinforced hollow metal doors. For Exit Only device, specify 8-1024 SNB (No. 10-24). For device with trim, specify 2-1024 SNB (No. 10-24). See page 9.</li></ul>	
Electric Functions	<p>Can be interfaced with building security systems:</p> <ul style="list-style-type: none"><li>• AL Alarm Exit</li><li>• DE Delayed Egress Device</li><li>• ELR Electric Latch Retraction</li><li>• LM Latch Bolt Monitoring</li><li>• RX Request to Exit</li><li>• SS Signal Switch</li></ul> <p>See page 37.</p>	
Device Centerline from Finished Floor	<ul style="list-style-type: none"><li>• 39-5/8" (1006mm).</li></ul>	
Latchbolt	<ul style="list-style-type: none"><li>• Stainless Steel, deadlocking, 3/4" (19mm) throw.</li></ul>	
Handing	<ul style="list-style-type: none"><li>• Trim field reversible.</li><li>• Device non-handed except for Double Cylinder option. For Double Cylinder, specify handing when required.</li></ul>	
Cylinders	<ul style="list-style-type: none"><li>• NOT furnished standard, specify when required. For Cylinder details, see page 31.</li></ul>	
Trim	<ul style="list-style-type: none"><li>• The device &amp; trim are sold separately, easy to mix and match, see page 21.</li></ul>	