

I-TEK Architectural
Locks & Hardware



B Series
ANSI Grade 2
Medium Duty
Cylindrical Locks
I/C Type

**Grade 2
B Series**

**Medium Duty
Cylindrical Locks
I/C Type**

I-TEK Architectural
Locks & Hardware

FEATURES

- Cylindrical designed, for medium and light duty commercial buildings.
- Interchangeable core knobs are easy to change handing.
- Threaded outside rose adjustable for various door thickness.
- Internal steel mechanisms are corrosion treated for normal atmospheric conditions.
- Wide selection of finishes and functions.

SPECIFICATIONS

Door Thickness	1 3/8" to 2" thickness wood or metal door installation.
Backset	2 3/4" standard, 2 3/8", 3 3/4" and 5" optional.
Latchbolt	1/2" throw, UL listed, faceplate self-adjusted.
Handing	Completely reversible.
Strike	T-strike standard, ANSI strike or Full lip strike optional.
Trim	Roses are wrought brass, bronze or stainless steel, installed over wrought steel mounting plates. Knobs are brass or bronze secured by steel knob retainer which cannot be depressed when lock has been locked.
Door Preparation	2 1/8" cross bore, 1" edge bore.
Master Keying	Can be masterkeyed or grand masterkeyed.
Interchangeable Core	6 or 7-pin, Compatible with Best [®] and Falcon [®] small format interchangeable cores.
Finishes	605, 606, 612, 613, 625, 626, 629 and 630.
Functions	Entry / Office Lock (01), Store Door Lock (02), Classroom Lock (03), Communicating Lock (04), Storeroom Lock (05), Institutional Lock (09), Connecting Room / Exit Lock (63).
Certifications	UL listed for "A" label (3-hour) single swinging door (4' x 8'). Listed in BHMA Directory of Certified Locks and Latches as conforming to ANSI A156.2, Series 4000, Grade 2.
Knob Design	Ball and Tulip optional.